PARTS LIST:

D

ITEM	QTY	QTY	PART NUMBER	DESCRIPTION	
	-107	-107B			
	Х		D205-596-107	CROSSTUBE ASSEMLBY, HI-HI AFT	
		Х	D205-596-107B	CROSSTUBE ASSEMLBY, HI-HI AFT, 214	
1	1	1	D6008-180	CROSSTUBE	
2	2		D2940-1	SUPPORT	
3	4	4	D3595-063-530	RUBBER CUSHION	
4		2	D5018-1	SUPPORT, 214 AFT	
5		4	MS21920-28	CLAMP	
6		A/R	PROSEAL 890 B-2	SEALANT (OR AMS-S-8802 CLASS B-2)	

GENERAL NOTES:

1) MATERIAL: MANUFACTURE FROM D6008-180 FINISHED LENGTH = 127.28 ± 0.02

2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1

PRIME INSIDE AND OUTSIDE PER DART QSI 005 4.2
PAINT OUTSIDE PER DART 005 4.2

3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED

4) UNITS: INCHES UNLESS OTHERWISE NOTED

5) BREAK SHARP EDGES: N/A

6) IDENTIFICATION: SCRIBE DART PART NUMBER AND BATCH NUMBER IN THIS AREA WITH VIBRATING STYLUS

7) WEIGHT: 50 lbs

8) PART IS SYMMETRIC ABOUT CENTERLINE

- 9) BEND PROGRESSIVELY WITH A MINIMUM OF 3 PASSES. MAXIMUM TUBE FLATTENING DUE TO BENDING IS 6% BASED ON O.D.
- 10) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE.
- 11) TO INSTALL D2940-1 / D5018-1 SUPPORTS: ABRADE MATING SURFACE OF SUPPORT AND CROSSTUBE WITH 180-GRIT SANDPAPER AND REMOVE RESIDUE WITH MEK (OR EQUIVALENT). APPLY A 0.04" TO 0.07" THICK LAYER OF PROSEAL 890 CLASS B-2 (OR AMS-S-8802 CLASS B-2) SEALANT TO MATING SURFACE OF SUPPORT.

<u>\(\) \(\) \(\) \(\)</u>

В

- 12) INSTALL MS21920-28 CLAMPS WITH D3595-063-530 RUBBER CUSHIONS TO SECURE D2940-1 SUPPORT. ENSURE CLAMP MECHANISMS ARE ON TOP SIDE OF CROSSTUBE.

 NOTE: IT IS ACCEPTABLE TO SUBSTITUTE MS21920-28 CLAMPS WITH LONGER OR SHORTER MS21920-XX CLAMPS TO ACCOMODATE VARYING DIAMETERS. ENSURE THERE IS A MINIMUM OF 1.5 THREADS IN SAFETY ON THE NUTS.
- 13) TORQUE CLAMPS 80 TO 100 IN-LB. ENSURE AT LEAST 1.5 THREADS SHOWING IN SAFETY AND THAT NUT HAS NOT BOTTOMED-OUT AFTER TORQUING. PRIOR TO PACKAGING, RE-CHECK TORQUE ON CLAMPS AFTER PROSEAL 890 SEALANT HAS CURED FOR 72 HOURS.

2018 JAN 24 47 ECN 18-525

С	REFORMAT, ADD SHT 3, HEIGHT/WIDTH DIM & TOL CHG, ADD TOTAL WIDTH DIM (B4-2, B4-3), CLAMP ORIENTATION FLIPPED (A5-2, A5-3), INCORP DEO'S						
В	1009 AE	RT NOW MAGN BRASION STRIF D3595-063-530	МВ	07.12.03			
Α	NEW IS	SUE	DS	02.11.20			
REV.	DESCRIPTION				DATE		
DESIGN			DART AEROSPACE LTD				
DRAWN		P	HAWKESBURY, ONTARI	O, CAN	ADA		
CHECKED		AS5	DRAWING NO.		REV. C		
MFG. APPR.		K	D205-596-107	;	SHEET 1 OF 3		
APPROVED		WM ()H	TITLE		SCALE		
DE APPR.		4	CROSSTUBE ASSEMBLY, I	H-H A	FT NTS		
17.08.23			COPYRIGHT © 2002 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.				

7 6

3

1



